

# 125mm Grommet Box

## FB125-003

# INTRODELTA<sup>LTD</sup>



#### TECHNICAL SPECIFICATION:

	<b>125mm</b>
Overall diameter of bezel:	140 mm
Fixing hole required:	127 mm
Flange depth below surface:	80 mm
Depth of connection back-box:	43 mm
Bezel thickness above surface:	3 mm
Inside diameter of flange:	111 mm
Max. cable diameter:	18 mm

## Description

The floor box consists of an outer case, which push-fits into a circular aperture provided in the raised floor.

The floor box has a top-assembly which is snapped into an upper receiving flange. The top assembly has a cover which rotates to reveal three 20 mm holes. Cables are passed through the holes prior to the top assembly being inserted within the outer case.

An accessory plate is located 30 mm beneath the top assembly cover. The accessory plate is held down by two screws secured into the outer case.

Two knockouts (1 x 20, 1 x 25mm) are provided on the base and the side of the connection box area beneath the accessory plate.

#### COLOURS

Black, or Grey.

#### Standard Plate Options:

Standard plates provide the facility for the following installations - 4 x shuttered RJ45 sockets (A) or 6 x un-shuttered RJ45 sockets (B) or 1 x un-switched 13 amp socket (C) or a blanking plate (D).